



COLORIFICIO VENEZIANO

the Art of
Paint

VELATURA 900

Decorative Line

Description

VELATURA 900 is excellent for obtaining shaded, veiled and ancient effects. It is very resistant to atmospheric agents, water, it preserves a good wall breathability and it is elastic. It has a glazed and velvet effect and can be applied on new, old and already painted plasters.

Thecnical data

- Specific weight: 1.060 kg/l +/- 5%
- Result: 15m22/l according to the desired effect
- Dilution: can be used pure or diluted with 10% water maximum, according to the final result.
- pH value: between pH 6.5 and pH 7.5
- Viscosity: (Brookfield rot. n. 4a 20 Rpm), 8,000 cps with +21 °C
- Water vapor permeability: Sd 0.25 m (Maximum permitted 2 m, DIN 52 615)
- Emission limit for organic ompounds: A/I; VOC: 30 g/l (maximum)
- Packages: 14, 5, 2.5 and 1.0 liters

Characteristics

VELATURA 900 is a decorative coating formed of resins in water emulsion and special metal pigments for the realization of many decorative finishing.

Base preparation

The surface must be clean and dry. Remove any grease and oil spot. If the base is chalky, apply **ISOLANTE ALTA PENETRAZIONE**, while if it is smooth use **FONDO**

RUVIDO.

To complete the base preparation apply one layer of **FONDO VELATURA METALLICA**, a special kind of stucco paste.

Application

After preparing the base, you can apply **VELATURA 900**.

According to the desired effect, there are several application techniques:

- **GRASSELLO 600** effect: use a steel spatula
- Ancient effect: use a brush or a roll

VELATURA 900 is used as decorative painting for indoor and outdoor use

It is colorable with Colorificio Veneziano's or universal coloring. Dilute with 10% water.

Warnings

- Apply the material only on dry and seasoned surfaces.
- Avoid the application during the coldest months.
- Apply with a temperature higher than +5 °C and lower than +35 °C.

Preservation

Avoid freeze. If stored inside the original package in proper environments, it lasts 1 year.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.