



COLORIFICIO VENEZIANO

the Art
of
Paint

ZETACRYL 72

Washable Hydro Painting

Technical data

- Dilution: Dilute the product with water; dilute the first layer at 35%, the second at 20%.
- Drying and Preservation: The drying process varies depending on the weather conditions. Avoid the preservation in very cold places. If stocked in proper places and inside the original package lasts 1 year.
- Result: The result depends on the supports, over two-coat plasters 4/5 m²
- Dry Waste: 69% +/-
- Specific weight: 1.454 kg/lt
- Supply colors: White or the colors from the palette.

Base preparation

The surface needs to be dry and clean, without dust, dirt, oil or any other greasy spots and must be completely clean. Before the varnishing cycle, wait at least 28 days from the application of the finishing plaster surface. In case of chalked or particularly absorbent plasters we suggest to apply the water acrylic insulating blend like **ISOEDIL-A** (or **MURISOL K**) diluted in a ratio of 1:5 with water or apply **ISOLANTE ALTA PENETRAZIONE** to be diluted 1:5.

We always suggest to use this treatment also when the surface you want to paint presents tough absorbance diversities.

Application

Brush or roll

Supply

Lt 14 and 5 litres.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.