



COLORIFICIO VENEZIANO

the Art of Paint

EL FERRO

Decorative Line

Description

Uses With the appropriate precautions, is possible use EL FERRO on:

Old synthetic or mineral paint Old plasters in lime or plaster Civil plasters New plaster with civil finishing Plasterboard surfaces It is not advisable to apply this type of finish over fresh mineral surfaces, as it may compromise the process of oxidation of the liquid activator. No apply in presence of humidity.

Characteristics

Technical features EL FERRO EL FERRO ATTIVATORE Product aspect paste liquid Dilution 5%-10% with water ready to use Application roller or brush sponge roller, brush, sponge or spray Yields 4-9 m²/kg 8/14 m²/lt (Yields can changes depending on the support and the final effect you want to obtain)

Other

Base preparation Clean the surface form powder or other impurity. If the surface present mold, pre-treat with a suitable liquid algaecide, called DETERGENTE ANTIMUFFA, eliminate any paintings in phase of detachment. When the surface is completely clean, apply the primer FONDO RUVIDO, to make the surface uniform without differences in absorption.

Product application When the surface will be completely dry, proceed with the application of EL FERRO and then, when the material will be perfectly dry apply a coat of EL FERRO ATTIVATORE, and a second hand in the necessary quantity to obtain the effect desired, more activator is applied, more intense will be the effect of oxidation.

Protection for the outside surfaces FINITURA FLOOR, MATT or GLOSS

Colors Not Colorable

Packing EL FERRO: 1 kg, 5 kg, 15 kg EL FERRO ATTIVATORE: 1 lt

Warnings It is advisable to complete each work with materials from the same batch production the material can be applied and stored at temperatures between +5 °C and +35 °C. If stored in the original container has a term of one year. At the end of the application properly clean the tools with water.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.