



COLORIFICIO VENEZIANO

the Art
of
Paint

WHITE FAST

Transpiring Hydro Painting

Description

WHITE FAST is a hydro painting formed of special emulsions, very covering charges and anti-mold additives. **WHITE FAST** is used for internal spaces and it has got an excellent coverage with the objective of preventing the formation of molds on walls. It offers great transpirability and it is very effective throughout time only if not covered with other paintings.

Thecnical data

- Specific weight: 1.518 kg/l
- Use: 130-170 g/m² per layer
- Result: 5-6 m²/l a when the two-hand work is over

Dull finishing for inside spaces, good for any kind of wall support finished with smooth finishing plaster, thin mortar or already treated walls. It gives homogeneity and a nice aesthetic aspect to the walls.

Base preparation

The surface needs to be dry and clean, without dust, dirt, oil or any other greasy spots and must be completely clean. Before the varnishing cycle, wait at least 28 days from the application of the finishing plaster. In case of chalked or particularly absorbent plasters we suggest to apply the insulating blend like **ISOEDIL-A** slightly diluted in a ratio of 1:5 with water or apply **ISOLANTE ALTA PENETRAZIONE**.

We always suggest to use this treatment when the surface you want to paint presents tough absorbance diversities.

Application

Dilution in weight with water: the first until 40%, the second 20%. Apply the second layer after 4 hours minimum from the first. The application can be done with a brush, with a wool roll and by airless spray-painting.

Supply

- 14 and 5 liters cans.
- Colors: white available. Under request warm pastel colors (see the colors folder).

Warnings

- Apply the material only over seasoned and dried plasters.
- Avoid the application during the coldest months of the year.
- Apply at a temperature higher than +5 °C and lower than +35 °C.

Other

Use

WHITE FAST is used as decoration and protection of finishing plasters for internal spaces and walls that have been previously painted.

Preservation

Avoid the preservation in very cold places. Preserve at temperatures higher than +5 °C and lower than +30 °C. If stocked in proper places lasts 1 year.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.