



COLORIFICIO VENEZIANO

the Art
of
Paint

FISSATIVO SILOXAN

Primers Line

Description

FISSATIVO SILOXAN is a water primer formed of special acryl-siloxane highly suitable with lime and cement plasters.

Thecnical data

- Specific weight: 1.000 kg/l
- Consumption: 100-150 g/m² (0.10 - 0.15 l/m²)
- Result: from 7 to 9 m²/l

Application

Dilute it in a 2:1 ratio with water.

Apply with brush or wool roll.

The application of paintings and coatings needs to be done at least 16 hours after the treatment.

Warnings

The temperature of +5 °C is the lowest value, +35 °C the highest for the application of **FISSATIVO SILOXAN**.

Other

Use

FISSATIVO SILOXAN is used as insulating material, fixative or base stabilizer before the finishing products application on paintings and wall coatings of the Hydro-siloxane Line without modifying the wall breathability.

Since it is a water product, can be used without hurting people's health both indoor and outdoor.

Preservation

Avoid freeze.

Preserve the product in right places. If stocked inside the original can it lasts 1year.

Quality

FISSATIVO SILOXAN is constantly and properly checked. The raw materials used are strictly selected and checked.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.