



FONDO T1

Primers Line

Description

White base used to obtain a smoother absorption for the preparation and insulation of new plasters. Thanks to its capacity to form a film membrane it is perfect for insulating chalk or thin mortars supports.

Technical data

- Application: brush, roll, air spray painting
- Number of layers: one
- Result: 10-0 m²/lt
- Drying-up: 30' to the touch (with +25 °C and 65% relative humidity), repaintable after 6 hours
- Solids: 24% ± 2
- Specific weight: 1.01

Characteristics

- Composition: high percentage of acrylic resins, thickeners, plasticizers, fermentation inhibitors properly measured and titanium dioxide.
- Features: high support penetration.
- Resistance features: resistant to alkali in urban, rural, marine and industrial environments.
- Dilution: dilute it in 1-5 liters of water each kg of **FONDO T1**, according to the support.

Supply

Standard packaging: 20 l, 10 l, 5 l

Colors: see folder.

THE REPORTED DATA REFER TO LABORATORY TESTS: DURING PRACTICAL APPLICATIONS IN BUILDING SITES THESE CAN BE SLIGHTLY MODIFIED ACCORDING TO THE CONDITIONS OF ANY INSTALLATION. THE PERSON WHO WORKS WITH THE PRODUCT MUST VERIFY THE EXPECTED SUITABILITY OF USE OF THE PRODUCT, TAKING UPON HIMSELF.

THE COMPANY COLORIFICIO VENEZIANO S.R.L. MAY CARRY OUT TECHNICAL ALTERATIONS ON PRODUCTS WITHOUT NOTICE.